



## Electrical characteristics

- Power current up to 700mA.
- Voltage range: from 28 V to 36 V.
- Electrical class: I & II.
- Standard electrical shock resistance: 6/10 kV (diff/comm).

## LED characteristics

- Type: CMS.
- Luminous flux maintenance: L90 B10 100 000 hrs.
- 3000K/4000K/2700K: CRI >70 - 2200K: CRI >80.
- ULR 6% (ULR: Upward Light Ratio).
- Photobiological hazard: RG0.

## Powers and luminous intensities

2200K Number of LED	Nominal flux <sup>(1)</sup> (lm)	Nominal eff. <sup>(1)</sup> (lm/W)	350 mA			500 mA			700mA			Energy efficiency class
			P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	
12	2940	175	15	985	66	20	1351	68	27	1835	68	E

  

2700K Number of LED	Nominal flux <sup>(1)</sup> (lm)	Nominal eff. <sup>(1)</sup> (lm/W)	350 mA			500 mA			700mA			Energy efficiency class
			P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	
12	3270	197	15	1111	75	20	1524	77	27	2040	76	E

  

3000K Number of LED	Nominal flux <sup>(1)</sup> (lm)	Nominal eff. <sup>(1)</sup> (lm/W)	350 mA			500 mA			700mA			Energy efficiency class
			P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	
12	3540	213	15	1201	81	20	1650	83	27	2209	82	D

  

4000K Number of LED	Nominal flux <sup>(1)</sup> (lm)	Nominal eff. <sup>(1)</sup> (lm/W)	350 mA			500 mA			700mA			Energy efficiency class
			P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	P <sub>t</sub> (W) <sup>(2)</sup>	Φ (lm) <sup>(2)</sup>	(lm/W) <sup>(2)</sup>	
12	3735	226	15	1270	85	20	1741	88	27	2331	87	D

(1) Maximum LED flux at operating temperature including driver consumption.

(2) Actual luminaire output data at operating temperature including driver consumption, optical accessories. A tolerance on the data is allowed in accordance with IEC 62717 and IEC 62722.

## Photometric distributions

### ASYMMETRICAL ROAD LIGHTING

#### ASY18 DORIX

