

Standard color  
Dark black RAL 9005



# MOUGINS

## LUMINAIRE'S SPECIFICATIONS

HERITAGE | MOUGINS



Dome made of stainless steel, copper or brass

IP68 vent

Luminaire's body

Model	Width	Height	Aerodynamic coefficient (C <sub>x</sub> S)	Weight
<b>Mougins 640</b>	430 mm	720 mm	0.100 m <sup>2</sup>	12 kg
<b>Mougins 650</b>	580 mm	900 mm	0.170 m <sup>2</sup>	14 kg
<b>Mougins 660</b>	620 mm	850 mm	0.200 m <sup>2</sup>	17 kg
<b>Materials</b>	Stainless steel			

**PROTECTION FINISH**  
Standard: Transparent  
Option: Diffuse white, frosted or droplets

**FIXING**  
Top mounted: on 3/4" BSPT male  
Suspended: 3/4" BSPT male

### Options



- Zhaga socket or Nema socket.

### Optical unit & control gear

8 to 64 LED module - From 1000 to 18400 lm (see EVO2 attached data sheet for details on power, light intensities and available photometries). Integrated smart driver (control, automatic adjustment, CLO, graduation via voltage variation or DALI). ULR < 1% (LED) (ULR: Upward Light Ratio).

<b>Materials</b>	ME (ME Resist on request)
<b>Electric class</b>	I and II
<b>Protection shape</b>	Standard: Bowl optical unit Option: Ogive bowl optical unit
<b>Protection index</b>	IP66
<b>Shock resistance</b>	IK09 IK10 (on request)

Operating temperature: -40°C to +35°C (up to +50° under conditions).

\*Regulation specific to France: Decree of 27/12/2018 relating to the prevention, reduction and limitation of light nuisance: product configuration to be defined according to the nature of the project.

18/09/2024 - All informations are subject to change without notice.

