

Standard color
Dark black RAL 9005



VENCE

LUMINAIRE'S SPECIFICATIONS

HERITAGE | VENCE



Dome made of stainless steel, copper or brass

IP68 vent

Luminaire's body

Model	Width	Height	Aerodynamic coefficient (CxS)		Weight
Vence 634	340 mm	720 mm	Optical unit	0.150 m ²	8.5 kg
			Flat glass	0.080 m ²	
Vence 638	380 mm	850 mm	Optical unit	0.170 m ²	10.4 kg
			Flat glass	0.090 m ²	
Vence 642	420 mm	870 mm	Optical unit	0.190 m ²	10.7 kg
			Flat glass	0.100 m ²	
Vence 645	450 mm	910 mm	Optical unit	0.210 m ²	11.5 kg
			Flat glass	0.110 m ²	

PROTECTION FINISH ————— or ————— clear flat glass
Standard: Transparent
Option: Diffuse white, frosted or droplets

FIXING
Top mounted: on 3/4" BSPT male
Suspended: 3/4" BSPT male

Optical unit & control gear

8 to 64 LED module - From 1000 to 18400 lm (see EVO2 attached data sheet for details on power, light intensities and available photometries). Integrated smart driver (control, automatic adjustment, CLO, graduation via voltage variation or DALI). ULR < 1% (LED) (ULR: Upward Light Ratio).

Materials	ME (ME Resist on request) or tempered glass
Electric class	I and II
Protection shape	Standard: 4-sided optical unit Option: Flat glass
Protection index	IP66
Shock resistance	IK08 IK10 (on request)

Operating temperature: -40°C to +35°C (up to +50° under conditions).

*Regulation specific to France: Decree of 27/12/2018 relating to the prevention, reduction and limitation of light nuisance: product configuration to be defined according to the nature of the project.

18/09/2024 - All informations are subject to change without notice.





634



638



642



645

Options

- Zhaga socket or Nema socket.
- Blackout face for heritage face luminaires.
- Wall-mounted half Vence:
 - Half VENCE 34
 - Half VENCE 38

